

# Speaker Management Systems

DPA Series - DPA440A

**DPA440A** is a High End 4-IN/4-OUT digital speaker management system. Designed for maximum versatility, it provides all the processing and control necessary for both live and fixed installation use. 4 analog inputs and 4 analog outputs are managed by a powerful MARANI® DSP Engine, for a full 96kHz processing, in addition to high performance 24 bit AD/DA Converters. Each input channel provides 13 PEQ, Gain control, Noise Gate, RMS Compressor, Internal White/ Pink Noise Generator, and configurable Delay. Each output offers 11 PEQ, in addition to the crossover filters which themselves provide slopes from 6 up to 48dB/Octave. Each output path also features Peak Limiter, RMS Compressor

and configurable Delay. The DPA440A supports two full matrix mixing mode where on the first matrix each input may be routed/mixed in any ratio to any output and on the second matrix each output channel may be routed/mixed in any ratio to any output. For remote configuration and control the DPA440A can be connected via USB or RS485 connections.

**DPA4448QRT**: it is a special version of the DPA440A, where the remote control can be selected between the USB connection on the front panel or the TCP/IP one, located on the Rear Panel, replacing the RS485.



## Features

### Outstanding Performance

Excellent sonic performance with 24bit high end converters coupled with 96kHz sample rate 4 inputs, 4 outputs with full matrix mixing

### Top-grade DSP Engine

13 band parametric equalization per input channel  
11 band parametric equalization per output channel  
Each band can be switched to Bell, Shelving, HP/LP, Band Pass, Notch Filter, All Pass  
Crossover filters with slopes from 6dB/Octave up to 48dB/ Octave including Butterworth, Bessel, Linkwitz-Riley  
12dB Headroom on internal overflow processes  
Each output features a precision dynamic range controller composed of a Limiter working on RMS value

of the limiter's input  
Adjustable Delay time up to 480 ms for every input channel and 270 ms for each output channel  
Phase correction per input and output channel

### Direct PC/Network Connection and Control

Rear panel USB connector for direct PC communications  
RS485 connection (DPA440A)/Ethernet Interface (DPA4448QRT) for system setup, monitoring and control via fully manageable remote PC software

Front panel interactive LCD display for local access and configuration  
Simultaneous control up to 32 units via PC software  
Up to 32 storable user presets  
Security Lockout

## Applications

- Auditoriums
- Houses of Worship
- Theaters
- Performing Art Centers
- Convention Centers
- Stadiums and Arenas
- Touring Musicians
- Stage Monitoring System digital

# Speaker Management Systems

DPA Series - DPA440A



## Audio

Analog Input	4 x XLR electronically balanced
Analog Output	4 x XLR electronically balanced
Minimum Load	150 ohm
THD+N	0.001% at 1kHz 0dBu
S/N	> 110dBA
Frequency Response	20Hz - 20kHz; -0.5dBu at 20Hz and 20kHz
AD & DA Converters	24bit - 96kHz

## DSP & Processing

DSP Engine	MARANI® DSP
DSP Resolution	24bit (data) x 24 bit (coeff.), 54 bit accumulation registers 96 bit precision on intermediate processing data
Parametric Equalization	13 PEQ filters per input; 11 filters per output
Master Gain	From -18dB to +12dB for input and output; by 0.1dBu resolution steps
Gain	From -30dB to 0dB for input and output; by 0.1dBu resolution steps
Filter Type	Bell, Shelving, HP/LP, Band Pass, Notch Filter, All Pass
Filter Gain	From -15dBu up to +15dBu by 0.5dBu resolution steps
Center Frequency	from 20Hz up to 20kHz with 1Hz resolution steps
Filter Q/BW	Bell Type: Q from 0.4 up to 128 in 100 steps Shelv/HP/LP Type: Q from 0.1 up to 5.1 in 100 steps BandPass/Notch Type/All Pass: Q from 4 up to 104 in 100 steps
Crossover Section	HPF/LPF ---- Butterworth 6/12/18/24/36/48dB per octave Bessel 12/24dB per octave Linkwitz-Riley 12/24/36/48dB per octave
2 Internal Noise Generator (to input 1/2 and to input 3/4)	White/Pink Noise; Level from -40dBu to 0dBu
Input Noise Gate	Threshold from -80dBu up to -50dBu, or not active Attack time from 1ms up to 1000ms; Release time from 10ms up to 1000ms
Input/Output RMS Compressor	Threshold from 20dBu up to -10dBu Ratio: 2:1~32:1; Knee: 0~100%; Makeup from -12dBu to +12dBu
Output Peak Limiter	Attack time from 5ms up to 200ms; Release time from 0.1sec up to 3sec Threshold from 20dBu up to -10dBu;
Delay	Attack time from 1ms up to 900ms; Release time from 0.1sec up to 5sec 480 ms 10.4us increment/decrement steps for each input, 270ms 10.4us increment/decrement steps for each output
Ground noise	-90 dBu

## General

Device Presets	32 User Presets
Dimensions	19" x 1.75" x 9" (483x44x229mm) 1RU
Weight. Net/Shipping	7.71 lbs (3.5 Kg) / 8.82 lb (4 Kg)