

MDA3-1000M is a highly flexible, powerful and intelligent 3-Channel power amplifier delivering up to a total of 3x1000W @ 4 ohms, or able to drive 70V Constant Voltage Lines, in Direct Drive without using internal transformers. Designed to meet the most demanding portable and fixed installation sound systems, it provides a full set of value added features such as high output power, efficient cooling system, on board DSP and USB/Ethernet for monitoring and control via PC software. MDA3-1000M includes a highly efficient Switch Mode Power Supply, which provides power to the output stages. The 3 output stages use the Class D module-full bandwidth PWM modulator obtaining ultra low distortion, high efficiency and also equipped with a full set of circuit protections. Furthermore the Clip/Limiter function provides output monitoring to prevent speaker damage with gentle gain reduction at clip threshold, in addition to the efficient heat dissipation system and

Over-Heat protection which themselves ensure uncompromised reliability. MDA3-1000M is more than just an amplifier. It is also a capable and sophisticated loudspeaker processor, thanks to its powerful MARANI® DSP running 96kHz/24bit [96 bits precision for the internal intermediate processes] and high performance 24bit AD/DA Converters. It offers 3 channels of slope up to 48dB/Oct IIR HP/LP crossover filters, or up to 512 taps FIR filters [FIR Coefficients can be imported as .txt files from external applications], RMS compressor, parametric Eqs, alignment delay and white/pink noise internal generator, everything needed to optimize a loudspeaker system. Moreover, MDA3-1000M allows a 12dB headroom process. User can also set the parameters, select input source, load presets, etc with the extraordinary touchscreen LCD in front panel. Apart from regular analog and digital source input, DANTE is also optional.



Features

Outstanding Performance

- High power output: 3 x 1000W @4 Ohm, 70V Direct Drive
- Highly efficient Switch-Mode Power Supply
- Class D Amp module-full bandwidth PWM modulator with ultra low distortion
- Excellent sonic performance with 24bit high end converters running 96kHz sample rate
- Full protection circuitry including Over-Current, Over/Under-Voltage, Output DC and Over-Temperature
- Support DANTE audio (optional)
- Warm Backup is available, by setting source priority and activating "Autoswithc" function in the PC SW

Top-Grade DSP Engine

- 12 band parametric equalization per input channel
- 4 band parametric equalization per output channel
- Each band can be switched to Bell, Lo/Hi-Shelving Q
- FIR or IIR Filters for X-Over:
- The X-Over can be implemented both by FIR filters or IIR
- HP/LP, selectable in the dedicated PC software
- FIR: Crossover filter with taps from 256 up to 512, the FIR

- type and the Out Band attenuation [FIR Coefficients can be imported as .txt/.csv file from external applications]
- IIR: Crossover filter with slopes of 6 ~ 48 dB/Oct, including Butterworth, Bessel, Linkwitz-Riley and customized topologies
- Each input channel includes a Pink/White noise internal generator, noise gate function, RMS compressor with variable knee
- Each output channel is equipped with a precise Peak Limiter
- Adjustable Delay time up to 500.998ms for input channel, and 340.998ms for output channel

Direct PC/Network Connection & Control

- Front panel USB connector for direct PC communications
- Ethernet interface for system setup, monitoring and control via manageable remote PC software
- Front panel interactive touchscreen LCD display for parametric setting, input source selection, preset loading and so on
- 50 Preset Selection



Power&Amplifier

Number of Channels	3
Max Output Power per Channel	1000W@4 ohms load, or 70V Direct Drive
Output Circuitry	Class D Amp Module- full bandwidth PWM modulator with ultra low distortion
THD+N	<0.01%
Signal To Noise Ration	> 105 dB (A-weighted, AES-17 filter)
Damping Factor	>580 (8Ω load, 1kHz and below)
Power Supply	Independent Switch mode Power Supply
Operating Range	110/220 VAC is selectable manually
Consumption / Current draw and Thermal dissipation @ 230 V	9.6W/018A/2.8BTU/H (Standby) 1083W/7.94A/317BTU/H (l/8 max. power@8Ω)
Protections	Over-Current, Over/Under Voltage, Output DC and Over-Temperature
Maximum Input/Output Level	+13 dB

Audio

Analog Input	2 x XLR electronically balanced, +13dBu
Frequency Response (DSP)	20 Hz - 20 KHz; -0.5dBu at 20 Hz and 20 kHz

DSP&Processing

DSP Engine	MARANI® DSP, 24 x 32 bit filter processing, 54bit accumulation registers, 96 bit precision on intermediate processing data
Parametric Equalization	12 band PEQ per input, 4 band PEQ per output, filter gain from -15 to +15dBu
Filter Type	Bell, Lo/Hi-Shelving, HP/LP, Band Pass, Notch Filter, All Pass
FIR for Phase Correction	Asymmetrical 512 Taps, with coefficients, allowing also FIR latency Adjustment/reduction. Coefficients can be generated by Pc Sw embedded Wizard tool, imported by external third party applications, and exported to third parties applications
Center Frequency	Selectable with a 0.5dBu resolution step from 20Hz up to 20kHz
Filter Q/BW	Bell: Q from 0.4 up to 128, steps: 100 Shelving: Q from 0.1 up to 5.1, steps: 100 Bandpass/Notch: Q from 4 up to 104, steps: 100
Input&Output Gain	-12dB ~ +12dB, resolution: 0.1dBu
IIR Crossover section HPF/LPF	Butterworth 6/12/18/24/36/48dB per octave; Bessel 12/24dB per octave; Linkwitz-Riley 12/24/36/48dB per octave.
FIR Crossover section HPF/LPF	Hp/Lp/Bp filters, Taps from 256 up to 512, Attenuation up to -120dB, Window type as Rect / Sinc / Keiser / Hanning / Hamming / Blackman / Nuttall / Sine
Noise Generator	Type: White/Pink Noise; Level: -40dBu ~ 0dBu
Input RMS Compressor	Threshold from -16dBu up to +14dBu; Ratio: 2:1~32:1; Knee: 0~100%; Attack time from 5ms up to 200ms; Release time from 0.1sec up to 3sec
Output Peak Limiter	Threshold from -16dBu up to +14dBu; Attack time from 1ms up to 900ms; Release time from 0.1sec up to 5sec
Internal Overflow Process	12dB Headroom
Delay	Each input has up to 500.998ms delay, each output has up to 340.998ms delay
Ground Noise	-86 dBu

General

User Preset	50
Front Panel	LCD display with Touchscreen Function 1 x Red LED (Power) 1 x Rotary encoder push button switches USB type B connector
Real Panel	3 x XLR female connector (Input) 3 x Neutrik® Speakon NI4 (Output) 1 x Ethernet 10/100 TCP-IP(PC Control) 2 x Ethernet 10/100 TCP-IP(Dante Audio Signal:Optional) 1 x Locking PowerCON® 20A: AC Power Cord (Blue) 1 x 80*80 mm 24V FAN
Dimensions	482X314.5X88mm
Weight, Net / Shipping	1.80 Kg / 13.00 Kg